

**Amendments to the Claims:**

A listing of the entire set of pending claims (including amendments to the claims, if any) is submitted herewith per 37 CFR 1.121. This listing of claims will replace all prior versions, and listings, of claims in the application.

**Listing of Claims:**

1. (Original) A method of determining proximity of a target node to a source node, comprising:
  - communicating a query from the source node to the target node,
  - communicating a response from the target node to the source node,
  - the response from the target node including a measure of processing time required to generate the response based on the query,
  - receiving the response at the source node,
  - determining a measure of query-response time between communicating the query and receiving the response, and
  - determining the proximity of the target node based on a communication time that depends upon a difference between the measure of query-response time and the measure of processing time.
2. (Original) The method of claim 1, wherein
  - the query and response correspond to at least a portion of a cryptographic key-exchange protocol.
3. (Original) The method of claim 2, wherein
  - the key-exchange protocol corresponds to a Needham-Schroeder key-exchange protocol.
4. (Original) The method of claim 1, wherein
  - the query and response correspond to at least a portion of an OCPS protocol.
5. (Original) The method of claim 1, wherein

the measure of processing time at the target node is predefined.

6. (Original) The method of claim 1, wherein

determining the proximity includes comparing the communication time to a threshold value that distinguishes between local and remote nodes.

7. (Original) The method of claim 1, further including

restricting communications with the target node based on the proximity.

8. (Original) The method of claim 1, wherein

the response is cryptographically signed by the target node.

9. (Original) A node on a network including:

a communication device that is configured to receive a query from a source node and to transmit a corresponding response to the source node,

a processor that is configured to process the query and produce therefrom the response,

wherein

the response includes a measure of processing time required to process the query and produce the response.

10. (Original) The node of claim 9, wherein

the processor is configured to process the query and produce the response as part of a cryptographic key-exchange protocol.

11. (Original) The node of claim 10, wherein

the key-exchange protocol corresponds to a Needham-Schroeder key-exchange protocol.

12. (Original) The node of claim 9, wherein

the query and response correspond to at least a portion of an OCPS protocol initiated by the source node.

13. (Original) The node of claim 9, wherein  
the measure of processing time is predefined.

14. (Original) The node of claim 9, wherein  
the processor is further configured to cryptographically sign the response.

15. (Original) A node on a network including:  
a communication device that is configured to transmit a query to a target node  
and to receive a corresponding response from the target node,  
the response from the target node including a measure of processing  
time required to generate the response at the target node, and  
a processor that is configured to:  
generate the query,  
receive the response,  
measure a query-response time between generating the query and  
receiving the response, and  
determine a proximity of the target node relative to the node based on a  
communication time that is dependent upon a difference between the query-  
response time and the measure of processing time.

16. (Original) The node of claim 15, wherein  
the processor is configured to generate the query and receive the response as  
part of a cryptographic key-exchange protocol.

17. (Original) The node of claim 16, wherein  
the key-exchange protocol corresponds to a Needham-Schroeder key-  
exchange protocol.

18. (Original) The node of claim 15, wherein  
the query and response correspond to at least a portion of an OCPS protocol  
initiated by the node.

19. (Original) The node of claim 15, wherein  
the measure of processing time is predefined.

20. (Original) The node of claim 15, wherein  
the processor is configured to determine the proximity based on a comparison  
of the communication time to a threshold value that distinguishes between local and  
remote nodes.

21. (Original) The node of claim 15, wherein  
the processor is further configured to control subsequent communications with  
the target node based on the proximity.